

– DIESEL GENERATING SET

– POWERED BY CUMMINS NTA855-G1A

TC315T 315 KVA

INDUSTRIAL STANDBY & PRIME
POWER SOLUTION



SILENT TYPE



OPEN TYPE

STANDBY (ESP)

315

KVA // 253 kW

PRIME (PRP)

288

KVA // 230 kW

VOLTAGE // 3Φ

400_v

454 A @ 50 Hz

NOISE @ 7M

≤ 78 ± 2

dB(A) // Silent

ELECTRICAL SPECIFICATIONS

01 // ELECTRICAL

| | |
|-------------------------|--------------------|
| Model | TC315T |
| Frequency | 50 Hz |
| Phases / Wires | 3 Phase, 4 Wire |
| Voltage | 400 / 230 V |
| Rated Current | 454 A |
| Rated Speed | 1500 r/min |
| Power Factor (cos φ) | 0.8 |
| Fuel Consumption @ 100% | 61.3 L/h |
| Engine | Cummins NTA855-G1A |
| Alternator | Stamford HCI 444D |
| Control Module | DSE 7320 MKII |

WEIGHT & DIMENSIONS

02 // PHYSICAL

– OPEN TYPE

L 3050 ×
W 1100 ×
H 1900 mm

3009 KG

Tank: 421 L

– SILENT TYPE

L 4366 ×
W 1406 ×
H 2260 mm

4134 KG

Tank: 600 L

STANDARDS GB/T 2820-2009 // ISO 8528 // CE // CNAS // IAF

– STANDARD INCLUDED

Engine, alternator, cooling system, base frame (excl. fuel tank), shock absorber, air intake, control box with mains floating charge, plastic fan blades.

– OPTIONAL ADD-ONS

Base frame with fuel tank, water jacket heater, fuel water separator, fuel heater, level sensors, switch box, auto-fueling system, battery frame, anti-condensation heater.

– ACCESSORIES BUNDLED

Silencer, bellow, exhaust silencing system accessories (matching engine), battery, starting cord assembly, gen-set documentation, tools matched to engine.

ENG.

MANUFACTURER: CUMMINS // 6-CYLINDER IN-LINE // TURBOCHARGED & AFTER-COOLED

POWER PLANT

4-STROKE DIESEL

291 KW @ 1500 RPM

CUMMINS NTA855-G1A

ENGINE CORE

01 // POWER PLANT

| | |
|---------------------------|--|
| Manufacturer | CUMMINS |
| Model | NTA855-G1A |
| Engine Speed (rated) | 1500 RPM |
| Cylinder / Arrangement | 6 / L (Inline) |
| Displacement | 14.0 L |
| Bore × Stroke | 140 × 152 mm |
| Compression Ratio | 14.0 : 1 |
| Max Standby Power @ Rated | 291 kW |
| Frequency Regulation | ≤ 1 % |
| Governor Type | Electrical |
| Aspiration / Cooling | Turbocharged & After-Cooled |

FUEL / OIL / AIR

02 // CONSUMABLES

| | |
|-------------------------------|-------------------|
| Fuel Consumption @ 100% PRP | 61.3 L / h |
| Fuel Consumption @ 75% PRP | 46.1 L / h |
| Fuel Consumption @ 50% PRP | 31.4 L / h |
| Fuel Consumption @ 25% PRP | 17.5 L / h |
| Total Oil Capacity w/ Filters | 38.6 L |
| Engine Air Flow | 379 L/s |
| Exhaust Gas Flow | 936 L/s |
| Exhaust Temperature | 498 °C |
| Max Back Pressure | 10 kPa |
| Radiator & Engine Capacity | 61.0 L |
| Max Water Temperature | 104 °C |

– KEY ENGINE ADVANTAGES

- ▶ **Cummins engines:** advanced design, reliable performance and durable continuous operation.
- ▶ High combustion efficiency and low fuel consumption, engineered for continuous running.
- ▶ Globally available Cummins service parts and authorised service network.
- ▶ Alloy-steel block and connecting rods for high durability under load.
- ▶ P/T pump injection technology — low cost and complete combustion.
- ▶ Proven platform operating across industrial, construction and agricultural applications.

ALT.

MANUFACTURER: CUMMINS GENERATOR TECHNOLOGIES // BRUSHLESS AVR //

IP23

CLASS H

3-PHASE AC

BRUSHLESS SHUNT

IP23 / CLASS H

STAMFORD HCI 444D

CORE CONFIGURATION

01 // BUILD

| | |
|----------------------|------------------------|
| Manufacturer | STAMFORD |
| Type | HCI 444D |
| Number of Phases | 3 |
| Power Factor (cos φ) | 0.8 |
| Pole Count | 4 |
| Bearing | 1 (Single) |
| Coupling | Direct |
| Exciter Type | Brushless SHUNT |

ELECTRICAL / PROTECTION

02 // PROTECTION

| | |
|------------------------------|---------------------------|
| Insulation Class / Temp Rise | H / H |
| Degree of Protection | IP 23 |
| AVR Model | AS440 |
| Altitude Rating | ≤ 1000 m |
| Winding Pitch | 2/3 |
| Winding Leads | 6 / 12 |
| Voltage Regulation | ± 1.0 % |
| Overspeed Capability | 2250 r/min (1 min) |

– STAMFORD ALTERNATOR QUALITY PROGRAM

- ▶ Utilising wire-wound (random-wound) technology — industry benchmark for all gen-set configurations.
- ▶ IP21, IP22, IP23 and IP44 enclosure protection options available.
- ▶ Manufactured under ISO 9001 and ISO 14001 certified environments.
- ▶ Brushless excitation with AVR — maintenance-free, high-reliability voltage control.
- ▶ Ideal for marine/offshore, UPS, telecoms, construction and continuous/standby power.
- ▶ Licensed service network across Southeast Asia for parts and warranty support.

STANDARDS GB755 // BS5000 Part 3 // VDE 0530 // NEMA MG1-22 // IEC-34 // CSA C22-100 // AS1359

CTRL.
 AUTO START & AUTO MAINS FAILURE (AMF) CONTROL MODULE // IP65 //
 ETHERNET-READY

AMF + AUTO START
GEN-SET CONTROLLER

IP65 / 250-EVENT LOG

DEEPSEA DSE 7320 MKII

PHYSICAL SPECS

01 // DIMENSIONS

| | |
|-------------------------|---------------------------------|
| Overall Size | 240 × 181 × 42 mm |
| Overall (imperial) | 9.4" × 7.1" × 1.6" |
| Panel Cutout | 220 × 160 mm |
| Panel Cutout (imperial) | 8.7" × 6.3" |
| Weight | 400 g |
| Ingress Protection | IP65 (with gasket) |
| Display | 132 × 64 px • 4-line LCD |
| Inputs / Outputs | 9 / 8 Configurable |
| Event Log | 250 Events |
| Operating Temperature | -30 to +70 °C |

MKII ENHANCEMENTS

02 // UPGRADES

| | |
|--------------------|---------------------------|
| Processing Power | Upgraded CPU |
| USB Host Port | Type-A (Firmware) |
| USB Device Port | Type-B (PC Config) |
| Front Editing | PIN Protected |
| Config Suite | v2 Compatible |
| Tier 4 CAN Support | Enhanced |
| Backward Mounting | Identical Cutout |
| Languages | Multi-lingual |
| DSENet® Expansion | Supported |
| Real-Time Clock | Battery Backed-up |

– CORE FEATURES

- 4-Line back-lit LCD text display
- Five-key menu navigation
- Front panel editing with PIN protection
- Customisable status screens & power save
- Up to 3 remote display units
- Tier 4 CAN engine support
- CAN & Magnetic Pick-up sensing
- Integral PLC editor

– PROTECTION & MONITORING

- kW & kVAr protection
- Reverse power (kW & kVAr) protection
- Unbalanced load protection
- Independent earth fault trip
- Charge alternator failure alarm
- Fuel usage monitor & low-fuel alarms
- LED and LCD alarm indication
- 3 configurable maintenance alarms

– LOAD & POWER CONTROL

- Automatic load transfer (AMF)
- Load shedding & dummy load outputs
- Power monitoring (kWh, kVAr, kVAh)
- Manual speed control (CAN engines)
- Manual fuel pump control
- Engine exerciser schedule
- Idle control for starting & stopping
- Multiple date/time scheduler

– CONNECTIVITY & SOFTWARE

- USB host + device connectivity
- RS232 & RS485 communications
- Configurable Gencomm pages
- Remote SCADA monitoring via PC software
- Advanced SMS messaging (start/stop via SMS)
- Ethernet via DSE860/865 modules
- Licence-free DSE Config Suite PC software
- DSENet® expansion compatible